




LCD Projector Details:

Sr. No.	Model	Made	Key Features	View of Projector
01	IN104 Mobile DLP Projector	INFocus	<ul style="list-style-type: none"> • 2700 ANSI Lumens • 1500:1 Contrast Ratio • XGA (1024 x 768) Native Resolution • DLP DMD Panel by Texas Instruments • No Filter Design Saves Time and Money • 720p 1080i, 1080p High Definition • NTSC, PAL, SECAM • 24/7 Non-Stop Duty Cycle • Standby Mode Draws Less Than 1 Watt • Lightweight and Compact 	
02	PT LB50EA- XGA	Panasonic	<ul style="list-style-type: none"> • Power supply: 100–240 V AC, 50/60 Hz • Power consumption: 240 W (Approx. 2 W in standby mode with fan stoped) • LCD Panel size: 4:3 aspect ratio, micro lens array • Display method: Transparent LCD panel (x 3, R/G/B) • <u>Pixels</u> • PT-LB50NTEA/LB50EA: 786,432 (1,024 x 768) x 3, total of 2,359,296 pixels • PT-LB50SEA: 480,000 (800 x 600) x 3, total of 1,440,000 pixels • Pixel configuration : Stripe • Lens: Manual zoom (1:1–1:1.2), manual focus, 1.6 –1.9, f 18.8– 22.6 mm • Colours: Full colour (16,777,216 colours) • Lamp: 165 W UHM™ lamp • Contrast: 400:1*1 (full on/full off) • Brightness: 2,000 lumens • Uniformity: 85% 	

03	VPL-DX100 - XGA	Sony	<ul style="list-style-type: none"> • PANEL 0.63(1.60 cms) x 3 BrightEra LCD panel Aspect ratio : 4:3 PROJECTION SYSTEM 3 LCD panels, 1 lens projector system • LIGHT OUTPUT 2300 lm (Lamp mode: high) / 1800 lm (Lamp mode: Standard) / 1500 lm (Lamp mode: low) • INPUT B HDMI input connector : HDMI 19-pin, HDCP support, Audio input connector : HDMI audio support • INPUT A RGB /Y Pb PR input connector : Mini D-sub 15-pin (female), Audio input connector : Stereo mini jack (shared with VIDEO IN) • CONTRAST RATIO 2500:1 	
s04	EB-W06 WXGA 3LCD	Epson	<ul style="list-style-type: none"> • 3,700 lumens • 3LCD technology for equal white & colour light output • WXGA resolution • Long lamp life up to 12,000 hours*² in ECO mode • Easy setup and positioning flexibility • HDMI connectivity 	